



# Econo-Mono

**Compliance:** *Econo-Mono* complies to ASTM C 1116-10.

**Product Description:** *Econo-Mono* is a medium duty fibre that offers good bonding, long term durability and improved toughness.

**Applications:** *Econo-Mono* provides an excellent low dose, steel free crack control solution for house slabs, toppings, driveways, footpaths and most general purpose concrete slab on ground applications.

**Benefits:** *Econo-Mono* is designed to provide excellent resistance to plastic and shrinkage cracking.

**Material Properties:**

**Material:** 100% virgin homopolymer polypropylene

**Fibre Count:** 32,000,000/kg

**Form:** Monofilament fibre

**Length:** 19mm.  
10mm and 13mm on request

**Specific Gravity:** 0.91

**Acid/Alkali Resistance:** Excellent

**Tensile Strength:** 600MPa

**Absorption:** Nil

**Packaging and Storage:** *Econo-Mono* is packaged in 0.6kg mulchable bags.  
30 x 0.6kg bags/box  
12 boxes/pallet.  
Recommended storage is a dry covered area.

**Performance:** Dose rate - 0.6kg/m<sup>3</sup>

**Mixing Procedure:** Add Fibres with additives. If assistance required click on *Mixing Procedure* or contact ReoCo directly.

**Technical Advice:** If assistance with design or dose rates is required, please contact a ReoCo Representative.

Darren Farmer  
Sales Manager  
0400 199 283  
ReoCo Head Office  
+61 2 4648 6300

Rev 2