



ReoPave25

Compliance: *ReoPave25* complies to ASTM A820 and NSW RTA R83/8.

Product Description: *ReoPave25* is a loose Type 1 cold drawn fibre to be used for concrete reinforcing and crack control in almost any situation.

Applications: *ReoPave25* is suitable for use in roundabouts, roads, slab on grade, precast, and dry shotcrete. Areas of high impact.

Benefits: *ReoPave25* is used to improve impact strength, fatigue resistance and concrete toughness.

Material Properties

Material: Bright low carbon steel wire

Fibre Count: 7,530/kg

Form: Round wire hook shape

Length: 31mm

Diameter: 0.85mm

Specific Gravity: 7.93

Tensile Strength: 1000MPa to 1100MPa

Absorption: Nil

Packaging and Storage: *ReoPave25* is packaged in 10kg bags.
100 x 10kg bags/pallet
Or 1tonne bulk bags

Recommended storage is a dry covered area.

Performance: Dose rate - 20kg/m³ to 75kg/m³
Re3% value - 24% to 65%

Mixing Procedure: Add Fibres with additives. If assistance required click on *Mixing Procedure* or contact ReoCo directly.

Technical Advice: If assistance with design or dose rates is required, please contact a ReoCo Representative.

Darren Farmer
Sales Manager
0400 199 283
ReoCo Head Office
+61 2 4648 6300

Rev 2